



A - $\phi 58 \times 210 \text{mm}$



Simple and easy appearance, in line with contemporary aesthetic concept. The product has the structure and appearance design patent. The lamp body adopts high-pressure cast aluminum and aluminum alloy, the surface is coated with outdoor used powder, double anti-corrosion to extend service life. This lawn lamp series uses LED. High efficiency constant current driver, ensure the light source is maximum used.

FIELDS OF APPLICATION

Landscape, Facade, trees, palm trees, green areas

Item No.	Wattage	Lumen	Color Temperature	IP	Voltage	CRI	PF	Beam Angle
7024101MAS-27	10 W	151lm/W	2700K	IP65	24V	90	0.9	10°, 30°, 45°, 60°
7024101MAS-3	10 W	151lm/W	3000K	IP65	24V	90	0.9	10°, 30°, 45°, 60°
7024101MAS-4	10 W	151lm/W	4000K	IP65	24V	90	0.9	10°, 30°, 45°, 60°
7024101MAS-6	10 W	151lm/W	6000K	IP65	24V	90	0.9	10°, 30°, 45°, 60°
7220101MAS-27	10 W	151lm/W	2700K	IP65	220V	90	0.9	10°, 30°, 45°, 60°
7220101MAS-3	10 W	151lm/W	3000K	IP65	220V	90	0.9	10°, 30°, 45°, 60°
7220101MAS-4	10 W	151lm/W	4000K	IP65	220V	90	0.9	10°, 30°, 45°, 60°
7220101MAS-6	10 W	151lm/W	6000K	IP65	220V	90	0.9	10°, 30°, 45°, 60°
7024151MAS-27	15 W	151lm/W	2700K	IP65	24V	90	0.9	10°, 30°, 45°, 60°
7024151MAS-3	15 W	151lm/W	3000K	IP65	24V	90	0.9	10°, 30°, 45°, 60°
7024151MAS-4	15 W	151lm/W	4000K	IP65	24V	90	0.9	10°, 30°, 45°, 60°
7024151MAS-6	15 W	151lm/W	6000K	IP65	24V	90	0.9	10°, 30°, 45°, 60°
7220151MAS-27	15 W	151lm/W	2700K	IP65	220V	90	0.9	10°, 30°, 45°, 60°
7220151MAS-3	15 W	151lm/W	3000K	IP65	220V	90	0.9	10°, 30°, 45°, 60°
7220151MAS-4	15 W	151lm/W	4000K	IP65	220V	90	0.9	10°, 30°, 45°, 60°
7220151MAS-6	15 W	151lm/W	6000K	IP65	220V	90	0.9	10°, 30°, 45°, 60°

Technical Details

Light Source	Spike light
Driver	on/off, Dimmable Phase dimming, 1-10
Voltage	220-240V /24V
Life Span	35000Hr
Temperature	ta=20°C-50°C
Diffuser	-----

Product Details

Finish	Black
Material	Dia cast aluminum
Application	-----
Warranty	3 YEARS
Class	-----

LED life time		Operating time 1.000 h										
Lamp	Lumen Maintenance Factor	1	10	20	30	40	50	60	70	80	90	100
L80	50.000 h	1	0.96	0.92	0.88	0.84	0.80	0.76	0.72	0.68	0.64	0.60
L80	100.000 h	1	0.98	0.96	0.94	0.92	0.90	0.88	0.86	0.84	0.82	0.80

